

INTRODUCING PARADIGM'S SPECIAL EDITION (SE) SERIES

Simplicity and Elegance in Form and Function

From the #1 Loudspeaker Brand* ... A Beautiful Blend of Technology and Design Open the Door to the World of True High-End Audio

- Gorgeous real wood veneer cabinets
- 'Reference' quality drivers and components
- Designed and engineered to be a complete music and home theater solution
- Models include SE 1 (bookshelf/stand-mounted), SE 3 (floorstanding), SE Center, SE Sub
- Ultra-compact high-performance SE Sub easily converts from down-firing to front-firing configuration: 900 watts Dynamic Peak Power / 300 watts RMS Sustained
- All models available in Rosenut, Black Gloss

Not buying a new home or the car of your dreams right now? Staying home with friends and family – connecting and being entertained? When it comes to home entertainment, if you're looking for a well-priced mix of aesthetics and competitive performance, then the all-new Paradigm SE Series is the perfect choice. Here are some reasons why, and why Paradigm always comes out on top when choosing the 'right' home entertainment system ... and how Paradigm outperforms the competition in every category!

PRICE: No other speakers in this price range feature such stunning looks or performance!

PERFORMANCE: The SE Series combines award-winning technology from Paradigm's Monitor Series and its 'Reference' Studio Series ... the best of both with the emphasis on affordability:

- H-PTD™ high-efficiency pure-titanium dome tweeters with ferro-fluid cooling;
- S-PAL™ satin-anodized pure-aluminum bass/midrange cones with advanced suspensions;
- Mineral-filled polypropylene bass cones;
- Paradigm® Reference quality crossover components.

STYLE: Soft edges and clean lines, even the subwoofer has a compact 'easy-to-live-with' footprint ... our smallest subwoofer yet!

QUALITY: Real wood veneer cabinets on all models at this price? Unheard of!

VALUE: Paradigm® is the #1 Brand* in affordable high-end performance.



Shown: SE 3, SE Center, SE Sub in Black Gloss



SE Sub is easily configured to forward-firing from downward-firing for hidden installations.



PBK™
READY

Paradigm Perfect Bass Kit™ Digital Room Correction system

Special Edition
SE SERIES
Paradigm®

*#1 price/value. *Inside Track* annual nationwide dealer survey.

SPECIFICATIONS

	<i>SE 1 (Bookshelf)</i>	<i>SE Center</i>	<i>SE 3 (Floorstanding)</i>
Design	2-driver, 2-way bookshelf / stand-mounted	4-driver, 3-way center channel	4-driver, 2-1/2-way floorstanding
Crossover	2nd-order electro-acoustic at 2.0 kHz	2nd-order electro-acoustic at 2.1 kHz; 2nd-order electro-acoustic at 300 Hz	2nd-order electro-acoustic at 2.0 kHz; 2nd-order electro-acoustic at 600 Hz
High-Frequency Driver	25-mm (1 in) H-PTD™ high-efficiency pure-titanium dome, ferro-fluid damped/cooled	25-mm (1 in) H-PTD™ high-efficiency pure-titanium dome, ferro-fluid damped/cooled	25-mm (1 in) H-PTD™ high-efficiency pure-titanium dome, ferro-fluid damped/cooled
Midrange Driver	n/a	89-mm (3-1/2 in) S-PAL™ satin-anodized pure-aluminum cone, (1 in) voice coil, GRIP™ glass-reinforced injection-molded polymer chassis	n/a
Bass / Midrange Driver	140-mm (5-1/2 in) S-PAL™ satin-anodized pure-aluminum cone, 38-mm (1-1/2 in) voice coil, GRIP™ glass-reinforced injection-molded polymer chassis	n/a	140-mm (5-1/2 in) S-PAL™ satin-anodized pure-aluminum cone, 25-mm (1 in) voice coil, GRIP™ glass-reinforced injection-molded polymer chassis
Bass Driver(s)	n/a	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones, 25-mm (1 in) voice coil, GRIP™ glass-reinforced injection-molded polymer chassis	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones, 25-mm (1 in) voice coil, GRIP™ glass-reinforced injection-molded polymer chassis
Low-Frequency Extension*	45 Hz (DIN)	50 Hz (DIN)	40 Hz (DIN)
Frequency Response: <i>On-Axis</i> <i>30° Off-Axis</i>	±2 dB from 70 Hz – 20 kHz ±2 dB from 70 Hz – 15 kHz	±2 dB from 75 Hz – 20 kHz ±2 dB from 75 Hz – 17 kHz	±2 dB from 65 Hz – 20 kHz ±2 dB from 65 Hz – 15 kHz
Sensitivity – Room / Anechoic	88 dB / 85 dB	91 dB / 88 dB	93 dB / 90 dB
Suitable Amplifier Power Range	15 – 120 watts	15 – 130 watts	15 – 200 watts
Maximum Input Power†	75 watts	100 watts	140 watts
Impedance	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms
Dimensions (h x w x d) includes spikes on floorstanding model	27.9 cm x 16.5 cm x 21.6 cm 11-1/2 in x 6-1/2 in x 8-1/2 in	17.8 cm x 44.5 cm x 24.1 cm 7 in x 17-1/2 in x 9-1/2 in	86.4 cm x 16.5 cm x 25.4 cm 34 in x 6-1/2 in x 10 in
Weight (unpacked)	5.9 kg / 12.9 lb per speaker	9.4 kg / 20.7 lb per speaker	16.7 kg / 36.9 lb per speaker
High-Performance Speaker Stand	Paradigm S-30	n/a	n/a
On-Wall Brackets	MB-60	n/a	n/a

SPECIFICATIONS

SE Sub

Design	Single high-excursion driver, configurable down-firing / front-firing sealed enclosure, patented built-in Ultra-Class-D™ power amplifier, USB port for connection of optional Paradigm Perfect Bass Kit™ digital room correction system (<i>sold separately, see dealer</i>)
Amplifier: High-Current, Discrete Output	900 watts Dynamic Peak / 300 watts RMS Sustained; includes Paradigm's Digital Signal Processing (DSP) design
Amplifier Design Features	Auto on / off, soft clipping
Bass Driver	254-mm (10 in) CAP™ carbon-aramid-fiber polypropylene cone, oversize ceramic / ferrite magnets, 50-mm (2 in) 4-layer voice-coil, dual Nomex® spiders, AVS™ die-cast heatsink chassis
Low-Frequency Extension*	24 Hz (DIN)
Subwoofer Cut-Off Frequency	Variable 35 Hz – 150 Hz: Bypass option
Sub / Sat Phase Alignment	Variable 0° – 180°
Line-Level Input	RCA (L/R-Mono) for L / R Line-Out or Sub-Out / LFE-Out of receiver / processor or other line-level source
Dimensions (h x w x d) with feet <i>(NOTE: Feet must be used in every installation)</i>	29.1 cm x 27.9 cm x 27.9 cm / 11-1/2 in x 11 in x 11 in
Weight (unpacked)	6.4 kg / 14.1 lb.

*DIN 45 500 Indicates -3 dB in a typical listening room.

†With typical program source, provided the amplifier clips no more than 10% of the time.

Stands and wall-mounting brackets sold separately.

